

Elevator Products 🔬 ce

Features

ABS engineering plastic material resistant to ageing, impact, corrosion & non conductive to heat unlike metal enclosure

Fire retardant

Robust & total maintenance free

IP65 Protection

Fully insulated to house electrical & electronic equipment w.r.t. protection against electric shock

Temperature Resistance from -20°C to 70°C

Pit Switches





Part No.	Type of Switch	Type of Contact	No's of Contact	Cable Gland	Qty. of Cable Gland	Protecting Shroud	Mounting Bracket
JMJB0000	Mushroom Head Push Pull	NC	1	PG 13.5	2	NA	MS Yellow Passivation
JJJE0000	Mushroom Head Push Pull	NC	2	PG 13.5	1	NA	MS Yellow Passivation
JLFB0000	Mushroom Head Push Turn	NC	1	PG 13.5	2	1	MS Yellow Passivation
JKFE0000	Mushroom Head Push Turn	NC	2	PG 13.5	1	1	NA
JKFB0000	Mushroom Head Push Turn	NC	1	NA	NA	1	NA
JQFB0000	Mushroom Head Push Turn	NC	1	PG 13.5	1	1	NA

Car Top Box



Features

Wall mounted

Available with Cam Switch

4 Way Push Button Station				
Cat. No.	EJ4C3AN028			

Customized Solutions - Car top box



Note: For your customized / special requirement of car top box please contact our sales team.

LED Solutions

Features

Customized solution for different elevator applications
Low power consumption

LED's with long life of close to 0.1 million continuous burning hrs

Passes surge test 2kV & HV test of 1.5kV
Low power consumption
-20°C to 70°C

LED Torch

LED Torch with Hook

High Illumination LED Torch



	LED Torch without Hook	LED Torch with Hook	High Illumination LED Torch
Cat. No.	IL24L55	IL24L40	IL16N42W240A
Colour (8 th Digit)	W - V		
	024 C - 24		
Voltage (9 th ,10 th , 11 th & 12 th Digit)	110 A - 1		
	240 A - 2	240 V AC	



Car Light



Car L	_ight
Cat. No.	IL07K27W240A

LED with Magnet



LED with Magnet				
Voltage	Cat. No.			
240V AC	IL06A00W240A			
110V AC	IL06A00W110A			

Emergency lighting



Product	Cat. No.	Color	Voltage
8 LED Strip	LT00G08	White	12 V DC
12 LED Strip	IL12A05W012D	White	12 V DC
15 LED Strip	IL15B13W012D	White	12 V DC
3 LED	IL03N39W012D	White	12 V DC

Note: Also available in 24V DC/6V DC

